

## Technology kit for Ecolift and Pumpfix F



### Article information

Item no.: 20000-TK  
 GTIN: 4026092097151  
 Price group: 30

### Description

Technology kit for Ecolift and Pumpfix

Consisting of control unit, pump, motor and 2 optical probes.

Cable length: 5 m

#### Dimensions

Net weight: 15 kg  
 Gross weight: 15,45 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: SPZ 1000  
 Number of pumps: 1  
 Weight, pump: 10 kg  
 Connection type: coded plug  
 Rated current: 5,2 A  
 Protection class: I  
 Insulation class: F  
 Cos phi - power factor: 0,97  
 Protection class (pump): IP 68 (3m/48h)  
 Temperature monitoring: integrated  
 Max. temperature (permanent) of conveyed material: 40 °C  
 Max. pumping capacity: 11,5 m<sup>3</sup>/h  
 Max. pumping height: 10 m  
 Speed: 2800 U/min  
 Power P1: 1,2 kW  
 Power P2: 0,69 kW  
 Operating mode: S3 - 50 %

Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Macerator
Length of mains cable for pump:	5 m
<b>Control</b>	
Control unit:	Comfort
Standby power:	5 W
Alarm sensor:	optical probe
Level measurement instrument:	optical probe
Type of level measurement:	optical
Protection class control unit:	IP 54
Operating voltage:	230 V
Connection type:	coded plug
Length of mains cable for control unit:	1,4 m
Potential-free contact:	yes
GSM interface:	no
USB interface:	no
Log book function:	yes
Multi-line display:	yes
Battery buffering:	yes
Self-diagnosis system (SDS):	yes
Type of fuse required (electrical protection):	C 16 A