

## Pump drive SPF 1500 400 V, S3, 5 m cable



### Article information

Item no.: 28028  
GTIN: 4026092058657  
Price group: 90

### Description

Pump drive with multi-vane impeller for wastewater w/ sewage

#### General characteristics

Type of wastewater: with sewage  
ATEX: no

#### Dimensions

Net weight: 24 kg  
Gross weight: 27,03 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Pumping device

Pump: SPF 1500  
Connection type: Direct connection  
Rated current: 2,7 A  
Protection class: I  
Run dry safe: yes  
Protection class (pump): IP 68 (3m/48h)  
Temperature monitoring: controlled via control unit  
Max. temperature (permanent) of conveyed material: 40 °C  
Max. pumping height: 8 m  
Speed: 1415 U/min  
Power P1: 1,4 kW  
Power P2: 1,1 kW  
Operating mode: S3 - 50 %  
Type of pump connection cable: H07RN-F 7G 1.5 mm<sup>2</sup>  
Length of mains cable for pump: 5 m

#### Control

Mains frequency: 50 Hz

Operating voltage:  
Connection type:  
Rated current:

400 V  
Direct connection  
2,7 A