

## Pump drive SPF 1500 400 V, S3, 5 m cable



### Article information

Item no.: 28028  
 GTIN: 4026092058657  
 Price group: 90

### Description

Pump drive with multi-vane impeller for wastewater w/ sewage

#### General characteristics

Type of wastewater: with sewage

#### Dimensions

Net weight: 24 kg  
 Gross weight: 27,03 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: SPF 1500-S1  
 Connection type: Direct connection  
 Protection class: I  
 Run dry safe: yes  
 Protection class (pump): IP 68 (3m/48h)  
 Temperature monitoring: controlled via control unit  
 Max. temperature (permanent) of conveyed material: 40 °C  
 Max. pumping height: 8 m  
 Speed: 1415 U/min  
 Power P1: 1,4 kW  
 Power P2: 1,1 kW  
 Operating mode: S3 - 50 %  
 Type of pump connection cable: H07RN-F 7G 1.5 mm<sup>2</sup>  
 Length of mains cable for pump: 5 m  
 Rated current: 2,7 A

#### Control

Mains frequency: 50 Hz  
 Operating voltage: 400 V

Connection type:

Direct connection