


Submersible pump Aquadive KTP 300 without float switch, 10 m



Article information

Item no.: 28740
 GTIN: 4026092000908
 Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

KTP 300 submersible pump without float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

General characteristics

Material:	Polymer
Standard:	EN 12050-2
Type of wastewater:	without sewage
Cable length:	10 m

Dimensions

Net weight:	4,33 kg
Gross weight:	4,69 kg
Length:	275 mm
Width:	390 mm
Height:	216 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Pumping device

Pump:	KTP 300
Number of pumps:	1

Weight, pump:	4 kg
Connection type:	Schuko (earthed contact) 2-pin
Operating voltage:	230 V
Rated current:	1,6 A
Protection class:	I
Insulation class:	F
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	6 m
Speed:	2800 U/min
Power P1:	0,34 kW
Power P2:	0,21 kW
Operating mode:	S1
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Length of mains cable for pump:	10 m
Control	
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A