

## Replacement pump KTP 300 for Minilift



### Article information

Item no.: 28836  
GTIN: 4026092000922  
Price group: 90

### Description

Replacement pump for sewage-free wastewater

#### Variant

Pump control: Float switch

#### General characteristics

Standard: EN 12050-2  
Type of wastewater: without sewage  
Cable length: 5 m

#### Dimensions

Net weight: 4,21 kg  
Gross weight: 4,49 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Pumping device

Pump: KTP 300  
Connection type: Schuko (earthed contact) 2-pin  
Operating voltage: 230 V  
Mains frequency: 50 Hz  
Protection class: I  
Insulation class: F  
Protection class (pump): IP 68 (3m)  
Temperature monitoring: integrated  
Max. temperature (permanent) of conveyed material: 35 °C  
Max. pumping height: 6 m  
Speed: 2800 U/min  
Power P1: 0,34 kW  
Power P2: 0,21 kW  
Operating mode: S1

Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Length of mains cable for pump:	5 m
Rated current:	1,9 A
Control	
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A