

Basement drain DN 100, Black grating, Class K 3



Article information

Item no.: 29111 GTIN: 4026092007846 Price group: 10

Advantages

- Integrated odour trap
- Including sludge bucket

Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Variant Contents of sludge trap: Position of lateral connection: Sealing water height: Discharge rate (l/s) with 20mm threshold:	yes Type II 60 mm 1,8
General characteristics Standard: Nominal size (DN): Outer diameter (OD): Odour trap:	EN 1253-1 100 110 mm included
Dimensions Vertical adjustment: Net weight: Gross weight: Cutout dimension, width: Cutout dimension, length: Installation depth: Type of height adjustability: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:	30 - 90 mm 2,55 kg 2,88 kg 320 mm 400 mm 216 - 276 mm vertically adjustable upper section 380 mm 290 mm length width height
Tank/drain body Inlet nominal size (DN):	70 mm

IK KESSEL

Number of inlets: Material of drain body: Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Frame material: Locking: Load class: Rim width: Rim length: Upper section material: Contents of sludge trap: 2 PP lateral

Slotted cover Polymer black 188 mm 188 mm Polymer placed K 3 (EN 1253-1) 200 mm 200 mm Polymer yes