

Yard drain System 100, vertical, round, B 125



Article information

Item no.: 67111B
 GTIN: 4026092039380
 Price group: 10

Advantages

- Recyclable
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

Variant

| | |
|--------------------------|-----|
| System: | 100 |
| Contents of sludge trap: | yes |

General characteristics

| | |
|--------------------|-----|
| Nominal size (DN): | 100 |
| ATEX: | no |
| Odour trap: | no |

Dimensions

| | |
|----------------------|---------|
| Net weight: | 2,33 kg |
| Gross weight: | 2,71 kg |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|-------------------------|----------|
| Number of outlets: | 1 |
| Material of drain body: | Polymer |
| Socket version: | vertical |

Coverage features

| | |
|-----------------|---------------------|
| Type of cover: | Round slotted cover |
| Cover material: | Ecoguss |

| | |
|--------------------------|----------------|
| Colour of cover: | black |
| Width of cover: | 247 mm |
| Length of cover: | 247 mm |
| Surface: | EDM |
| Locking: | Lock & Lift |
| Load class: | B 125 (EN 124) |
| Shape of upper section: | round |
| Upper section material: | Ecoguss |
| Contents of sludge trap: | yes |