


## Replacement pump pumping station dry installation SPF 4500-S3



### Article information

Item no.: 680533  
 GTIN: 4026092074947  
 Price group: 90

### Description

Replacement pump type SPF 4500-S3 for Aqualift F XL pumping station, dry installation

#### Variant

Pump control: Control unit

#### General characteristics

Cable length: 10 m

#### Dimensions

Net weight: 26,5 kg  
 Gross weight: 29,3 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: SPF 4500-S3  
 Connection type: Direct connection  
 Operating voltage: 400 V  
 Mains frequency: 50 Hz  
 Protection class: I  
 Insulation class: F  
 Cos phi - power factor: 0,85  
 Protection class (pump): IP 68  
 Temperature monitoring: controlled via control unit  
 Max. temperature (permanent) of conveyed material: 40 °C  
 Max. pumping height: 20 m  
 Speed: 2850 U/min  
 Power P1: 4,2 kW  
 Power P2: 3,5 kW  
 Operating mode: S3 - 50 %

Type of pump connection cable:	H07RN-F 7G 1.5 mm <sup>2</sup>
Length of mains cable for pump:	10 m
Rated current:	7,5 A
Control	
Operating voltage:	400 V
Connection type:	Direct connection
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V