

Replacement pump Aquadive SPF1300 230 V



Article information

Item no.: 680535
 GTIN: 4026092075012
 Price group: 90

Description

Replacement pump, Aquadive, SPF 1300 for faecal wastewater

Variant

Pump control: Control unit

General characteristics

Type of wastewater: with sewage
 Cable length: 5 m
 ATEX: no

Dimensions

Net weight: 9,39 kg
 Gross weight: 10,3 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: SPF 1300
 Number of pumps: 1
 Weight, pump: 10 kg
 Connection type: Direct connection
 Operating voltage: 230 V
 Mains frequency: 50 Hz
 Rated current: 6,4 A
 Protection class: I
 Insulation class: F
 Cos phi - power factor: 0,98
 Protection class (pump): IP 68
 Temperature monitoring: integrated
 Max. temperature (permanent) of conveyed material: 35 °C
 Max. pumping height: 9,2 m

Speed:	2600 U/min
Power P1:	1,5 kW
Power P2:	0,91 kW
Operating mode:	S3 - 10 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Length of mains cable for pump:	5 m
Control	
Connection type:	Direct connection