

## Replacement pump SPF 2900 400 V, S3, 5 m cable



### Article information

Item no.: 681247  
GTIN: 4026092109663  
Price group: 90

### Description

Pump drive with multi-vane impeller for wastewater with sewage.

#### Dimensions

Net weight:	11,3 kg
Gross weight:	11,8 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Pumping device

Pump:	SPF 2900
Weight, pump:	11,3 kg
Connection type:	Direct connection
Operating voltage:	400 V
Protection class:	I
Insulation class:	F
Protection class (pump):	IP 68 (3m/48h)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Max. pumping capacity:	44 m <sup>3</sup> /h
Max. pumping height:	14 m
Speed:	2700 U/min
Power P1:	3,1 kW
Power P2:	2,4 kW
Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN8-F 6G 1 mm <sup>2</sup>
Impeller type:	Multi-vane impeller
Free passage:	40 mm
Length of mains cable for pump:	5 m
Rated current:	5 A

#### Control

Operating voltage:	400 V
Connection type:	Direct connection
Type of fuse required (electrical protection):	C_20_A