


## Backwater valve Staufix DN 150, exposed, Type 1



### Article information

Item no.: 720150  
 GTIN: 4026092076088  
 Price group: 10

### Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

### Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

#### Variant

Emergency closure: yes  
 Mechanical backwater flaps: 1

#### General characteristics

Colour: black  
 Standard: EN 13564  
 Nominal size (DN): 150  
 Outer diameter (OD): 160 mm  
 Type of wastewater: without sewage  
 Installation situation: exposed drainage pipe  
 Delivery state: installation-ready  
 Backwater protection: Type 1

#### Dimensions

Net weight: 3,2 kg  
 Gross weight: 3,97 kg

Vertical drop between inlet and outlet:	8 mm
Length:	523 mm
Width:	216 mm
Height:	306 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Coverage features	
Type of cover:	Lockable cover
Cover locking:	One-handed closure