

Backwater valve Staufix Basic DN 125, Type 1, with emergency closure



Article information

Item no.: 72125

GTIN: 4026092002360

Price group: 10

Advantages

- Simple conversion possible using conversion kits
- Optional rat protection flap for additional safety
- Fast and toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second backwater flap.

Variant

Stainless steel flap as rat protection: no Emergency closure: yes Mechanical backwater flaps: 1

General characteristics

Colour: black
Standard: EN 13564
Nominal size (DN): 125
Outer diameter (OD): 125 mm

Type of wastewater: without sewage Installation situation: exposed drainage p

Installation situation: exposed drainage pipe Delivery state: installation-ready

Backwater protection: Type 1

Dimensions

Net weight: 2,2 kg
Gross weight: 2,2 kg
Vertical drop between inlet and outlet: 9 mm
Length: 405 mm
Width: 200 mm
Height: 280 mm
Packaging dimension: length



Packaging dimension: width Packaging dimension: height

Coverage features

Cover locking: Quick-release closure