


Backwater valve Staufix DN 90, exposed, Type 2





Article information

Item no.: 730090 GTIN: 4026092076293 Price group: 10

Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

Variant	
Stainless steel flap as rat protection:	no
Emergency closure:	yes
Mechanical backwater flaps:	2
General characteristics	
Colour:	black
Standard:	EN 13564
Nominal size (DN):	90
Outer diameter (OD):	90 mm
Type of wastewater:	without sewage
Installation situation:	exposed drainage pipe
Delivery state:	installation-ready
Backwater protection:	Туре 2
Dimensions	
	1 4 1
Net weight:	1,4 kg
Gross weight:	4 kg



Vertical drop between inlet and outlet: Length: Width: Height: Packaging dimension: Packaging dimension: Packaging dimension:

Coverage features Type of cover: Cover material: Colour of cover: Cover locking: 8 mm 385 mm 167 mm 230 mm length width height

Lockable cover Polymer black One-handed closure