

Staufix FKA conversion kit DN 100-200, fr. 01/2012, 15 m cable



Article information

Item no.: 80104
 GTIN: 4026092051344
 Price group: 30

Description

The conversion kit is equipped with a motor-driven closure system, which is closed automatically in the event of backwater. A second closure system serves as an emergency closure to be closed by hand.

The station is controlled by a user-friendly control unit, which is optionally integrated in the building management system via a potential-free contact, or alarm and collective fault messages can be output via a GSM interface.

The conversion kit is used to upgrade backwater chambers LW 1000 and backwater module chambers LW 1000 with the Staufix FKA backwater valve.

General characteristics

| | |
|----------------------------|--|
| Standard: | EN 13564 |
| Nominal size (DN): | 100-200 |
| Note on nominal size: | Hydraulics correspond to DN 150 |
| Type of wastewater: | for wastewater with and without sewage |
| Backwater protection: | Type 3 |
| Type de protection moteur: | IP 68 (3m/48h) |
| Cable length: | 15 m |

Dimensions

| | |
|----------------------|---------|
| Net weight: | 7,83 kg |
| Gross weight: | 8,82 kg |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Control

| | |
|--------------------------------|---------------|
| Control unit: | Comfort |
| Alarm sensor: | optical probe |
| Level measurement instrument: | optical probe |
| Type of level measurement: | optical |
| Protection class control unit: | IP 54 |

| | |
|---|----------|
| Length of mains cable for control unit: | 1,4 m |
| Potential-free contact: | optional |
| GSM interface: | yes |
| USB interface: | yes |
| Log book function: | yes |
| Multi-line display: | yes |
| Battery buffering: | yes |
| Self-diagnosis system (SDS): | yes |