

Grease separat. EasyClean Modular free, NS 3, Standard, 3-part, TS



Article information

Item no.: 93003-R2-TS GTIN: 4026092104002 Price group: 60

Advantages

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant	three-piece chamber
Chamber system:	Standard
Disposal variant:	no
Shredder-Mix-System:	no
Sludge bucket:	3,00
Nominal size (NS):	no
SonicControl:	no
Refill inlet in accordance with DIN 1988:	no
Type of disposal:	manual with suction hose
General characteristics	EN 1825
Standard:	free-standing installation
Installation situation:	Installation-ready (connection parts must be
Delivery state:	connected on site)
Dimensions Net weight: Gross weight: Height tank bottom up to centre section: Set-up area, height:	110 kg 128 kg 550 mm 1300 mm



1240 mm
1383 mm
580 mm
length
width
height
885 mm
955 mm
110 mm
100 mm
110 mm
100 mm
PE-HD pipes in accordance with DIN 19537, HT pipes
in accordance with DIN 19560, PP or AS
Cover
Polymer
black
Quick-release closure
odour-tight
420 l
720 l
300 l
120 l
no