

Grease separator EasyClean ground NS 10, Standard, 1120-1740 mm, Class D



Article information

Item no.: 93010/170D
 GTIN: 4026092073339
 Price group: 60

Advantages

- Vertically adjustable upper section with odour-tight cover plates in various load classes
- Waterproof, resistant to aggressive wastewater
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via one or several service access covers. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

| | |
|---|---------------------------------|
| Note on installation depth: | Version for deeper installation |
| Chamber system: | Cistern |
| Disposal variant: | Standard |
| Shredder-Mix-System: | no |
| Sludge bucket: | no |
| Nominal size (NS): | 10,00 |
| SonicControl: | no |
| Refill inlet in accordance with DIN 1988: | no |
| Type of disposal: | manual with suction hose |
| Load-bearing capacity (DIN 19901): | E4 |

General characteristics

| | |
|-------------------------|---|
| Material: | PE |
| Standard: | EN 1825 |
| Installation situation: | underground installation |
| Delivery state: | Installation-ready (connection parts must be connected on site) |

Dimensions

| | |
|-------------|--------|
| Net weight: | 488 kg |
|-------------|--------|

| | |
|--|---|
| Gross weight: | 510 kg |
| Groundwater resistant from lower edge of base section: | 1320 mm |
| Diameter: | 659 mm |
| DSC: | 700 - 1.500 |
| T-DSC: | 220 |
| Max. length: | 3062 mm |
| Installation depth: | 1120 - 1740 mm |
| Type of height adjustability: | vertically adjustable upper section, can be tilted by 5 degrees |
| Required access area, length: | 2910 mm |
| Required access area, width: | 1200 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Tank/drain body | |
| Distance pipe bottom outlet to tank bottom: | 1030 mm |
| Distance pipe bottom inlet to tank bottom: | 1100 mm |
| Outlet nominal size (OD): | 160 mm |
| Outlet nominal size (DN): | 150 mm |
| Inlet nominal size (OD): | 160 mm |
| Inlet nominal size (DN): | 150 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS |
| Clear width of entry (LW): | 800 mm |
| Coverage features | |
| Type of cover: | Cover plate |
| Cover material: | Grey iron |
| Colour of cover: | black |
| Height of cover: | 121 mm |
| Locking: | locked |
| Load class: | D 400 (EN 124) |
| Tightness: | odour-tight and surface water resistant |
| Wastewater contents | |
| Separator contents: | 1600 l |
| Total volume: | 2600 l |
| Contents of sludge trap: | 1000 l |
| Storage quantity of grease: | 400 l |
| Control | |
| Control unit: | no |