


## Grease separator EasyClean free NS 15, Standard, right



### Article information

Item no.: 93015-01-R  
 GTIN: 4026092105221  
 Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

#### Variant

|                      |                          |
|----------------------|--------------------------|
| Direction of flow:   | right                    |
| Disposal variant:    | Standard                 |
| Shredder-Mix-System: | no                       |
| Nominal size (NS):   | 15,00                    |
| SonicControl:        | no                       |
| Type of disposal:    | manual with suction hose |

#### General characteristics

|                         |   |
|-------------------------|---|
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |

#### Dimensions

|               |        |
|---------------|--------|
| Net weight:   | 355 kg |
| Gross weight: | 430 kg |

|                               |         |
|-------------------------------|---------|
| Set-up area, length:          | 3530 mm |
| Set-up area, width:           | 1680 mm |
| Set-up area, height:          | 1950 mm |
| Required access area, length: | 3530 mm |
| Required access area, width:  | 1490 mm |
| Required access area, height: | 1950 mm |
| Packaging dimension:          | length  |
| Packaging dimension:          | width   |
| Packaging dimension:          | height  |

#### Tank/drain body

|   |         |
|---|---------|
| Distance pipe bottom outlet to tank bottom: | 1130 mm |
| Distance pipe bottom inlet to tank bottom:  | 1200 mm |
| Outlet nominal size (OD):                   | 200 mm  |
| Outlet nominal size (DN):                   | 200 mm  |
| Inlet nominal size (OD):                    | 200 mm  |
| Inlet nominal size (DN):                    | 200 mm  |

#### Coverage features

|                  |             |
|------------------|-------------|
| Type of cover:   | Cover       |
| Cover material:  | Polymer     |
| Colour of cover: | violet      |
| Tightness:       | odour-tight |

#### Wastewater contents

|                              |        |
|------------------------------|--------|
| Separator contents:          | 2230 l |
| Max. grease layer thickness: | 180 mm |
| Total volume:                | 3730 l |
| Contents of sludge trap:     | 1500 l |
| Storage quantity of grease:  | 600 l  |